



NEW FROM SOLAX Triple Power 3.0



Triple Power 3.0 Battery

Features

- Systematic design, in-depth optimization and seamless connection with Solax Hybrid inverter
- Unique battery heating technology, which is capable to work at low temperature^①
- Safe type of LiFePO₄ battery, an adoption of high-performance processors
- Modular stacking design, easy installation, supporting floor mounting
- Auto power replenishment technology is adopted to prevent battery over-discharge
- IP65, supporting indoor and outdoor installation
- Remote fault diagnosis, upgrade and maintenance
- Multiple communication interfaces: RS485, CAN
- International brand devices, better stability
- Long life cycle, more than 6000 times
- Safety Cert. TUV, CE, UN38.3 and so on

① With Hybrid G4 inverter

info@solaxpower.com
service@solaxpower.com



For more information, please contact us

www.solaxpower.com
AU: +61 1300 476529
DE: +49 6142 4091664

Global: +86 571-56260008
UK: +44 2476 586998
NL: +31 (0) 852 737932

Triple Power 3.0



	T-BAT H 3.0 T-BAT H 3.0 V2	T-BAT H 6.0 T-BAT H 6.0 V2	T-BAT H 9.0 T-BAT H 9.0 V2	T-BAT H 12.0 T-BAT H 12.0 V2
Nominal voltage [V]	102.4	204.8	307.2	409.6
Operating voltage range [V]	90 ~ 116	180 ~ 232	270 ~ 348	360 ~ 464
Total energy [kWh]	3.1	6.1	9.2	12.3
Usable energy ^① [kWh]	2.8	5.5	8.3	11.0
Rated capacity [Ah]	30			
Nominal power [kW]	2.5	5.1	7.6	10.2
Max. power [kW]	3.1	6.1	9.2	12.3
Recommend charge / discharge current [A]	25			
Max. charge / discharge current [A] ^②	30			
Battery roundtrip efficiency	95%			
Cycle life [90% DOD]	6000 Cycles			
Expected life time / W arranty [year]	10			
Available charge / discharge temperature range [°C]	-30 to 50			
Storage temperature [°C]	-20°C~30°C (12 months) 30°C~50°C (6 months)			
Relative humidity [%]	4 ~ 100 (condensing)			
Altitude [m]	Below 3000			
Ingress protection	IP65			
Battery to Inverter	RS485 / CAN2.0			
Battery to battery /BMS	CAN2.0			
Master control capacity indicator	4 LED (25%, 50%, 75%, 100%)			
Master control LED indicator (Working mode)	1 LED			
System switch (on / off)	Buttonx1+Breakerx1			
Safety	CE, IEC62619, IEC62040, UKCA, VDE2510, RoHS			
UN number	UN3480			
Hazardous materials classification	Class 9			
UN transportation testing requirements	UN 38.3			
Dimensions (WxHxD) [mm]	MC0600: 482.5x173.5x153 HV10230: 482.5x471.5x153			
Net weight [kg]	MC0600: 7.5 kg +HV10230: 34.5 kg	MC0600: 7.5 kg +2xHV10230: 69 kg	MC0600: 7.5 kg +3xHV10230: 103.5 kg	MC0600: 7.5 kg +4xHV10230: 138 kg

① Test conditions: 90% DOD, 0.2C charger & discharger @+25 °C

② Max. charge / discharge current may be variant with different inverter models

V2.4. Information may be subject to modify without notice.