

51.2V 100Ah Energy Storage Battery



Safety Assurance

Compliant with UL9540A requirements, ensuring the safety of the entire battery pack even in the event of battery cell thermal runaway.

Remote Connectivity

Enables WiFi connection and cloud platform support for remote monitoring and management of the battery pack.

Remote Upgrade

Supports OTA remote online upgrade, ensuring ongoing support for future product function expansion and optimization.

Compact Size and Easy Installation

The module design enables quick installation.

Expandable at Need

Units can be combined to increase energy capacity.

Systematic Safety Design & Technologies

Multi-stage protection design enhances the safe storage; meets the standards of international safety certifications.

High Energy Density

The compact structure achieves marketing-leading energy density.

TECHNICAL DATA

Model	RESS-BM-051100-L1
Rated Voltage [V]	51.2
Rated Capacity [Ah]	100
Total Energy [kWh]	5.12
Charge Voltage [V]	57.6
Max. Charge/Discharge Current [A]	100A charge; 150A/6KW Discharge
Recommended Charge/Discharge Current [A]	50
Dimensions [W*D*H, mm]	440*420*130.5
Weight [Kg]	45
Cycle	>6000cycles
IP Grade	IP20
Charge Operating Temperature	0°C~50 °C*
Discharge Operating Temperature	-20°C~55 °C**
Relative Humidity	0%RH-95%RH
Communication Port	RS485,CAN
Certification	CE, IEC62619, UN38.3, UL1973, UL9540A, RoHS

*Derating occur between-10°C~10°C.

**Derating occur between-10°C~0°C,45°C~55°C.

SHENZHEN ACE BATTERY CO., LTD.

Email: sales@acebattery.com

Phone: +86 755 8887 8567

www.acebattery.com

©SHENZHEN ACE BATTERY CO., LTD. All rights reserved

ACE-RESS-ZE231200 | REV 01 | Nov. 2023

