

STACK314 NEW

16.08 kWh / Module, 241.14 kWh / System
Parallel up to 2.89 MWh



Compact Design, Flexible Deployment

Ultra Safe
Built-in aerosol fire extinguisher to eliminate fire risks

Max. continuous charge/discharge current

200A

Wiring-free stack-up, **plug-and-play**

Wide Operating Temperature Range

Battery Equalization
Free mixing of modules **within 3 years**

SPECIFICATION

Model	STACK314
Battery Type	LiFePO ₄ (LFP)
Nominal Battery Energy	16.08 kWh
Usable Battery Energy	15.28 kWh
Nominal Capacity	314 Ah
Nominal Voltage	51.2 V
Module Number per Cluster	3~15 Pcs
Operating Voltage	134.4 V~864 V
System Energy Range	48.228 kWh~241.14 kWh
Recommended Charge & Discharge C Rate	0.45C (140 A)
Max. Charge & Discharge C Rate	0.64C (200 A)
Peak Discharge Current (25°C)	280 A, 2min
Recommended Charge & Discharge Power	7.168 kW
Max. Charge & Discharge Power	10.24 kW
Depth of Discharge (DOD)	95%
Charging Temp. Range	-20°C~55°C
Discharging Temp. Range	-20°C~55°C
Net Weight (kg) ^[1]	38+115*n
Single Cluster Dimension (W/D/H) ^[2]	770/425/293+230*n
Protection Level	IP20
Communication	CAN/RS485
Cycle Life ^[3]	≥8000 Cycles
User Interface	WIFI+APP
afety Protection	Built-in aerosol fire extinguisher
Cooling Method	Forced wind cooling
Installation	Cable-free stacking
Expansion	Up to 12 clusters in parallel
Warranty Period ^[4]	10 Years
Battery Module Name	S51314
Certification & Safety Standard	UN38.3/CE-EMC/IEC62619
Compatible Inverters	ATESS/Deye/Growatt/Megarevo/Solinteg/Solis/Sosen/Sinexcel etc.

Module	SBDU200
Operating Voltage	134.4V~864 V
Maximum Continuous Current	200 A
Dimension (W/D/H)	770/425/160 mm
Weight	19.2 kg
Protection Level	IP20

[1] Net Weight of Expansion Base and Expansion Upper Cover: 18.5kg.

[2] Height of Expansion Upper Cover: 80mm, "n" stands for the number of battery modules, up to a maximum of 8. If the installation is on an upper floor, you will need to evaluate the floor weighing before determining the number of stacks.

[3] Test conditions: 0.2C Charging & Discharging, 25°C, 95% DOD, 70%EOL

[4] Refer to Dyness Warranty Letter

